

Wireless Flood Detector



- Transmission to a Carephone with Class 1 reception
- Reliable detection
- Flexible installation
- Wireless solution
- Automatic battery and radio link monitoring

The Wireless Flood Detector reacts upon detecting an entry of water or other conducting fluids. An alarm will be sent when a contact is made with a fluid height of 1 mm.

Functions

The signalization of alarms is made through LED indication and siren (85 dB at 1 m distance). Detection failures are indicated by a blinking LED and a specific siren tone. An automatic status monitoring is made by sending a signal to a Carephone every 23 hours, in which the radio link and the battery level are measured.

Parts included

Quantity	Component
1	Wireless Flood Detector
1	Power adapter
1	User manual

Technical specifications

Power supply	9V alkaline battery block IEC 6LR61 type
Power consumption in standby	< 16 µA without radio module
Power consumption during an alarm	< 20 mA without radio module
Operating temperature	0°C to +55°C, in a heated and dry environment
Storage temperature	-20°C to +60°C
Relative humidity	max. 80%
Acoustical indications	siren, typ. 85 dB (1m distance)
Optical indications	LED
Dimensions (H x W)	63 x 80 mm
Weight	Approx. 150 g
Material and color	White plastic

TeleAlarm SA
 Rue du Pont 23
 2300 La Chaux-de-Fonds
 Switzerland
info@telealarm.com
www.telealarm.com

TeleAlarm Europe GmbH
 Hertzstraße 2
 04329 Leipzig
 Germany
info-uk@telealarm.com
www.telealarm.com