



devolo

dLAN® 550 duo+

Technical data

| | |
|--|--|
| Standards | IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3x, IEEE 802.3az, IEEE 1901 Auto MDI/X HomePlug |
| Protocols | CSMA/CA (Powerline) |
| Transmission speeds | Ethernet 10/100 (mbps) Powerline 200/500 (mbps) |
| Modulation • Carrier | Powerline OFDM - 4096/1024/256/64-QAM, QPSK, BPSK • Powerline 2880 |
| Range (in m) | Powerline: 400 |
| Security | 128 Bit AES |
| LEDs | dLAN (multi) |
| Buttons | Pairing |
| Socket • Connector • Countries | Type G (BS 1363) • Type G (BS 1363) • (UK) |
| Power output to integrated socket | 13 A |
| Device port | 2 x Ethernet RJ45 |
| Power consumption | Maximum W/A: 3.1 W Typical W/A: 2.6 W Stand-By W/A: 0.6 W |
| Power supply | internal 196-250 V AC 50-60 Hz |
| Attenuation filter | 2 - 68 MHz |
| Filter characteristics | -22 db to -45 db |
| Temperature (Storage • Operating) | -25°C to 70°C • 0°C to 40°C |
| Dimensions (in mm, without plug) | 110 x 65 x 40 |
| Ambient conditions | 10-90% Humidity (non-condensing) |
| Operating systems | Windows 7 (32 Bit), Windows 7 (64 Bit) Windows 8.x (32 Bit), Windows 8.x (64 Bit) Ubuntu-Linux 14.04 (32 Bit), Ubuntu-Linux 14.04 (64 Bit) MAC OS X 10.10 |
| Certifications | CE Class B (EU, CH, NO) |



devolo

dLAN® 550 duo+

Sales information

| | |
|----------------------------|--|
| Warranty (in years) | 3 |
| Accessories | Printed Install Flyer Ethernet Cable(s) |

Single adapter

9292 (UK)

EAN: 4250059692923
Weight: 370 g
Dimensions: 190 x 118 x 80 mm

WEEE additional information:

Weight WEEE: 255 g
Paper (Green Dot): 110 g
Plastic (Green Dot): 4 g
other (Green Dot): 0.2 g

Starter Kit

9299 (UK)

EAN: 4250059692992
Weight: 685 g
Dimensions: 190 x 231 x 80 mm

WEEE additional information:

Weight WEEE: 510 g
Paper (Green Dot): 175 g
Plastic (Green Dot): 8 g
other (Green Dot): 0.4 g